



## T-217/GR RADIO TRANSMITTER



Radio Transmitter T-217/GR and its associated Modulator-Power Supply constitutes a 100 Watt Output UHF Ground Station Transmitter covering the Frequency Range of 225 to 399.9 mc. This Equipment is MFG by Collins Radio and part of Radio Sets AN/GRC-27 AN/TRC-32, & AN/ARC-29. The Companion Receiver for this Transmitter is the R-278/GR see page 5. This Transmitter is ideal for Airport Installation.

**TECHNICAL CHARACTERISTICS:**  
 Freq. Range: 225-399.9 mc A 3 & A 2 1020 CPS  
 Freq. Stability:  $\pm 0.01\%$   
 Freq. Control: 3r Crystals, Internal  
 Channels: 1750 Manual or 10 Preset  
 Channel Spacing: 100 kc  
 Power Output: 100 Watts  
 Microphone: Carbon  
 Output Impedance: 52 OHMS  
 Power Input: MD-129/GR 115/230V. AC. 50/60 CPS, 1 Phase  
 Dimensions: T-217/GR 12"H x 19"W x 20" D  
 Wt.: 130 Lbs., MD-129/GR 12" x 19" W x 20" D:  
 Wt.: 140 Lbs.

**Principal Components:**  
 T-217/GR Radio Transmitter Reconditioned Like New \$495.00  
 MD-129/GR MOD-Power Supply Reconditioned Like New 295.00

## AN/GRC-26 • SCR-399 RADIO SET




Radio Set AN/GRC-26 is a Mobile Self-contained Radio Teletypewriter, Voice-CW Communications Center which can be operated in motion or stationary. The principal components are: BC-610 Radio Transmitter-2-18 mc-400W see page 9. R-388/URR Radio Receivers .5-30.5 see page 3. PE-95 Power Plant see page 32.

AN/GRC-26 Ex. Cond. P. U. R.

Radio Set SCR-399 basically the same as AN/GRC-26 but does not have provisions for radio teletype. Also uses BC-342 Radio Receivers 1.5 to 18 mc see page 4.

SCR-399 Radio Set Ex. Cond. P. U. R.

## BC-610-E RADIO TRANSMITTER



The BC-610-E is a 2-18 mc High-Power AM & CW Transmitter MFG by the Hallicrafters Co. This Transmitter being the rugged Military version of the Famous Hallicrafters Model HT-4 the BC-610-E is widely used for all types of services requiring a efficient, & reliable medium Frequency rugged Transmitter.


**TECHNICAL CHARACTERISTICS:**  
 Freq. Range: 2-18 mc  
 Channels: 3  
 Output Power: 400 Watts CW, 300 Watts AM  
 Freq. Control: Crystal or Master OSC  
 Output Impedance: 73 OHM Balance Line  
 Microphone: Carbon-T-17 Dynamic-T-50  
 Power Input: 115V AC 50/60 CPS 1 Phase, 2 KW  
 Circuit: Two 100-th MOD, one 250-th PA. Class-C  
 Dimensions: 40"H x 22"D x 33"W Wt.: 400 Lbs.

**Principal Components:**  
 BC-610-E Radio XMTR with PA Coils, Tuning Units & Cables Recond Like New \$695.00  
 3C-939-A Antenna Tuning Unit " 65.00  
 3C-614-E Speech Amplifier " 35.00  
 Crystals MFG to order New each 4.00

WE CAN ALSO SUPPLY BC-610-H & BC-610-I

## BC-640

### RADIO TRANSMITTER




The BC-640 is a 50 Watt AM, CW or MCW Transmitter covering the Frequency Range of 100-156 mc preset Frequency determined by the Crystal installed. This Transmitter is particularly suited for installation at Airports for Ground to Air Communications. The BC-640 consists of seven chassis mounted in a six foot high enclosed Cabinet. The BC-640 is a rugged & reliable Transmitter designed by Bendix Radio, it is used with its Companion Receiver, the BC-639. See page 5

**TECHNICAL CHARACTERISTICS:**  
 Freq. Range: 100-156 mc AM, CW, or MCW  
 Power Output: 50 Watts  
 Preset Freq.: One  
 Freq. Control: Crystal  
 Output Impedance: 72 OHM  
 Microphone: Carbon T-17  
 Circuit: Two 811 class-B MOD, two 24-G class C-PA  
 Power Input: 115/230V AC, 50/60 CPS, 1 Phase 860W  
 Dimensions: 72"H x 20"D x 20"W Wt. 500 Lbs.

**Principle Components:**  
 BC-640 Radio Transmitter Ex. Cond. \$295.00  
 Crystals MFG to order New each 4.00  
 Ground Plane Antenna, cut to Freq. New 19.95  
 T-32 Desk Carbon Microphone Ex. Cond. 4.95

## AN/ARC-5 COMMAND TRANSMITTER SCR-274-N & ATA




The Command Series Group of Transmitters are one of most popular surplus groups of Transmitters in use to day. They are extremely versatile and easily adapted for Voice or CW putting out 50 Watts. The tubes used are 1 1625 Resonance Indicator, 1625 master OSC and 2 1625 Push Pull PA. The MD-7/ARC-5 is a class "B" Plate Modulator using 2 1625 which Modulate up to 50 Watts, and can be used with any Command Transmitter. Army & Army/Navy Units are interchangeable.

**Principal Components:**  
 ARMY ARMY/NAVY  
 None T-18/ARC-5 2.1-3.0 mc Ex. Cond. \$4.95  
 BC-696 or T-19/ARC-5 3-4 mc " 7.95  
 BC-457 or T-20/ARC-5 4-5.3 mc " 4.95  
 BC-458 or T-21/ARC-5 5.3-7 mc " 4.95  
 BC-459 or T-22/ARC-5 7-9.1 mc " 12.95

**Accessories:**  
 MD-7/ARC-5 Plate Modulator Ex. Cond. \$4.95  
 BC-456 Screen MOD " 3.95  
 XMTR Control Box " 1.50  
 Single XMTR MTG. Rack " 2.95  
 Specify BC or ARC-5  
 Dual XMTR MTG. Rack " 1.95  
 Specify BC or ARC-5  
 MOD MTG. Rack " 1.50  
 Connectors Specify which one's " 2.95  
 Antenna Relay " 2.95  
 24V. Dyn. for XMTR & Modulator Power " 2.95  
 12V. " " " " " 7.95

NOTE! We will ship whatever ARC-5 or BC units that are available at time of order, unless you specify not to do so..


## BC-653-A RADIO TRANSMITTER



The BC-653-A is a Medium Power Voice & CW Transmitter MFG by G.E., covering the Frequency Range of 2-4.5 mc. Any one of four preset channels can be easily selected at will. This Transmitter is ideal for Marine, or Amateur Installations. The Companion Receiver is the BC-652-A. See page 3

**TECHNICAL CHARACTERISTICS:**  
 Freq. Range: 2-4.5 mc  
 Power Output: Voice, 100 Watts CW  
 Freq. Control: Master Control  
 Preset Freq.: Four  
 Microphone: Carbon T-17  
 Circuit: One 1613 Screen MOD, one 814 PA.  
 Power Input: 12V. DC. @ 40 A or 24V. DC. @ 20 A  
 Dim.: 14"H x 26"W x 12"D Wt.: 143 Lbs.

**Principle Components:**  
 BC-653-A Radio Transmitter Ex. Cond. \$24.95  
 DM-42-A 12V. Dynamotor " 9.95  
 DM-43-A 24V. " 4.95  
 FT-253-A Mounting Rack " 4.95



# COLUMBIA Electronic Sales, INC.

4365 WEST PICO BOULEVARD • LOS ANGELES 19, CALIFORNIA • WEBSTER 8-3731

CABLE ADDRESS "COLECTRON" - OPEN MONDAY AND FRIDAY NIGHTS "TIL 9:00 P.M."